

GUANGZHOU VAIANO TEXTILES CO., LTD.

Address: No. 21 Zhuijiang Road,
Chigang Village, Shilou Town, Panyu,
Guangzhou, Guangdong, P.R. China
511447

Telephone: +86-20-8484-1158

Fax: +86-20-3486-2497

Web site: www.gvtextiles.com



For information contact:
Bruce Guan - bruce@pyurasia.com

Export sales office:
Rachel Peng - gildmore@ms21.hinet.net

Domestic sales office:
Amie Zheng - sales@gvtextiles.com

SPECIFICATION SHEET

L-Protection®: Q FLEX TX T6 MXC

Material description:

Non metallic textile insert for anti-puncture resistance in safety footwear.
Material designed for EN 12568:2010
This is a bonded multilayer complex material composed by three layers.

Specification:

Thickness: 3,90 mm (+/- 0.1mm)
Weight: 3900 gr. / sq. meter (+/- 3%)
Standard sheet size: 100 x 155 cm
Sheets per pallets: 150
Standard roll size: 800 x 155 cm
Minimum Adhesion: 3 N/cm

Certificates:

Q FLEX TX T6 MXC is certified to conform to CSA Z195 and ASTM F2413 norms with reference to zero penetration at 1200 N.

Q FLEX TX T6 MXC is certified to conform to EN 12568:2010 with reference to zero penetration at 1100 N.

PEAK FORCE 1900 N

(*) is considered "peak force" the force needed for the full passage of the nail through the insert.

The material meets the ESD conductive requirements

File: 227382

February 2019

Z195

ASTM F2413

EN 12568:2010

L - protection®

Q

FLEX TX
T6 MXC

